

QIS RANGE

50 - 60 Hz

*Gesan line, your solution
for Predictable Power*

Our QIS range of generators has been designed, manufactured and tested for a lifetime of service.



Atlas Copco

QIS RANGE 50 - 60 Hz

The QIS range is designed to combine maximum choice with exceptional reliability and performance.

From primary to critical backup power needs, these generators are designed for optimal performance in the most demanding conditions and all applications, from data centers and healthcare to manufacturing, utilities and retail.

Thanks to its versatility and user-friendliness, it can be easily integrated into all your projects.

Designed and built to the very highest standards, QIS range carries out extreme testing for both components and for the assembled units – resulting in exceptional reliability.

KEY BENEFITS

Easy installation	
Performance	
Noise attenuation	
Versatility	
Maintenance efficiency	

OPTIONS

The QIS range allows you to specify the configuration of your generator through a wide range of useful options. You can customize everything from the power output to the required level of noise suppression.

OPTIONS*	OPTIONS AS RETROFIT KIT*
<ul style="list-style-type: none"> o External fuel tank connection o Lifting beam o Earth leakage relay o High-capacity fuel tank up to 330kVA o GSM access via external module o Protective covers for hot parts (CE) o Battery isolator switch o Synchronizing control modules 	<ul style="list-style-type: none"> • Shock absorber mounts and spring isolators • Fuel filter with water separator • Remote monitoring and control via Webnet/3G/Ethernet • Remote display • Digital input/output expansion modules • Coolant heater • Battery charger

*Please contact us for additional information, options availability depends on models.

SEGMENTS





Maximal versatility and self configurability via its unique and easy to use self upgradeable, from single use to paralleling, control and power panel.
*Available from 220 kVA.



Works reliably in extreme temperatures.



Excellent accessibility and serviceability that allows easy cleaning of the radiator and convenient access to the alternator.



A single lifting point ensures safe, simple and well-balanced handling.



Installation-friendly design thanks to its dual-position air outlets. Front or top.



Smarter and safer installation with its vertical power cable outlet through the frame.



To be used in the most noise-sensitive areas. Different noise-attenuation level enclosures.



Excellent accessibility and superior serviceability. Large removable 45° doors from 65 to 330 kVA.



























Spillage-free frame, internal filling inlet. Easy and clean drainage of all liquids.



Tough, rust-proof canopy protects all components.

QIS 50 - 60 Hz

THE FULL RANGE

	50 Hz	60 Hz	50 Hz kVA Prime/ standby	50 Hz kW Prime/ standby	60 Hz kVA Prime/ standby	60 Hz kW Prime/ standby	50 Hz	60 Hz	
	QIS 10	QIS 10	9/10,2	7,2/8,2	11/12,6	8,8/10,1	QI 10	QI 10	
	QIS 16	QIS 15	13,8/16	11/12,8	16,6/18,8	13,3/15	QI 16	QI 15	
	QIS 25	QIS 19	20/21,5	16/17	23/23,5	18,4/18,8	QI 25	QI 19	
	QIS 35	QIS 30	30/32,5	24/26	34/36,5	27,2/29,2	QI 35	QI 30	
	QIS 45	QIS 45	42/46	34/37	51/54	40,8/43,2	QI 45	QI 45	
	QIS 65	QIS 60	60/66	48/53	70/77	56/62	QI 65	QI 60	
	QIS 95	QIS 90	85/95	68/76	102/114	82/91	QI 95	QI 90	
	QIS 115	QIS 100	105/115	84/92	120/130	96/104	QI 115	QI 100	
	QIS 140	QIS 120	130/143	104/114	140/155	112/124	QI 140	QI 120	
	QIS 220	QIS 200	200/220	160/176	230/241	184/193	QI 220	QI 200	
	QIS 330	QIS 300	300/330	240/264	325/341	260/273	QI 330	QI 300	
	QIS 470	QIS 400	410/470	328/376	450/500	360/400	QI 470	QI 400	
	QIS 510	QIS 450	460/509	368/407	526/563	421/450	QI 510	QI 450	
	QIS 580	QIS 500	524/580	419/464	572/625	458/500	QI 580	QI 500	
	QIS 630	QIS 540	571/630	457/504	642/680	514/544	QI 630	QI 540	
	QIS 700	QIS 610	635/700	508/560	692/764	554/612	QI 700	QI 610	
	QIS 735	QIS 710	680/735	544/588	808/893	646/714	QI 735	QI 710	
	QIS 830	QIS 740	752/830	601/664	849/925	679/740	QI 830	QI 740	

PREDICTABLE POWER

Atlas Copco Predictable Power brings customers in the on-site generator and power generation business peace of mind with solutions that combine low cost of ownership, reliable performance and risk-free operation. Predictable Power is our core value and the guiding principle for how we design, test, build, commission and service our generators.

Atlas Copco

Photos and illustrations contained here in might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice.
Not all products are available in all markets.