


THE Vertex

BACKSHEET MONOCRYSTALLINE MODULE



515W

MAXIMUM POWER OUTPUT

21.4%

MAXIMUM EFFICIENCY

0~+5W

BINNING TOLERANCE

PRODUCTS | POWER RANGE
TSM-XXXDE18M(II) | **495-515W**



High customer value

- Lower LCOE (Levelized Cost Of Energy), reduced BOS (Balance Of System) cost, shorter payback time
- Lower guaranteed first year and annual degradation
- Designed for compatibility with existing mainstream system components
- Higher return on Investment



High power Mono Perc up to 515W

- Large area cells based on 210mm silicon wafers and 1/3-cut cell technology
- Up to 21.4% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping effect, lower series resistance and improved current collection



High reliability

- Minimized micro-cracks with innovative non-destructive cutting technology
- Ensured PID resistance through cell process and module material control
- Resistant to harsh environments such as salt, ammonia, sand, high temperature and high humidity areas and fire class C
- Mechanical performance up to 5400 Pa positive load and 2400 Pa negative load



High energy yield

- Excellent IAM (Incident Angle Modifier) and low irradiation performance, validated by 3rd party certifications
- The unique design provides optimized energy production under inter-row shading conditions


Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates


IEC61215/IEC61730/IEC61701/IEC62716/UL61730
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupational Health and Safety Management System




Trina Solar's Vertex Backsheet Performance Warranty




DIMENSIONS OF PV MODULE(mm)




Front View




Back View



I-V CURVES OF PV MODULE(505 W)



P-V CURVES OF PV MODULE(505W)



ELECTRICAL DATA (STC) TSM-XXXDE18M(II) (XXX=495-515)

Peak Power Watts- P_{MAX} (Wp)*	495	500	505	510	515
Binning Tolerance- P_{MAX} (W)	0 ~ +5				
Maximum Power Voltage- V_{MPP} (V)	42.6	42.8	43.0	43.2	43.4
Maximum Power Current- I_{MPP} (A)	11.63	11.69	11.75	11.81	11.87
Open Circuit Voltage- V_{OC} (V)	51.5	51.7	51.9	52.1	52.3
Short Circuit Current- I_{SC} (A)	12.21	12.28	12.35	12.42	12.49
Module Efficiency η_m (%)	20.5	20.7	21.0	21.2	21.4

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.

*Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Maximum Power- P_{MAX} (Wp)	373	377	381	385	388
Maximum Power Voltage- V_{MPP} (V)	40.2	40.4	40.6	40.5	40.7
Maximum Power Current- I_{MPP} (A)	9.28	9.33	9.38	9.50	9.53
Open Circuit Voltage- V_{OC} (V)	48.4	48.6	48.8	49.0	49.2
Short Circuit Current- I_{SC} (A)	9.84	9.90	9.95	10.01	10.06

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	150 cells
Module Dimensions	2187×1102×35 mm (86.10×43.39×1.38 inches)
Weight	26.3 kg (58.0 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: 350mm/280mm(13.78/11.02inches) Length can be customized
Connector	Staubli MC4 EVO 2 / Trina Solar TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P_{MAX}	-0.34%/°C
Temperature Coefficient of V_{OC}	-0.25%/°C
Temperature Coefficient of I_{SC}	0.04%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC)
	1500V DC (UL)
Max Series Fuse Rating	20A

WARRANTY

12 year Product Workmanship Warranty
25 year Power Warranty
2% first year degradation
0.55% Annual Power Attenuation

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 31 pieces
Modules per 40' container: 620 pieces